



Section 1: IDENTIFICATION

Product Name: Gibson CGO

Synonyms: Petroleum Hydrocarbon; Combined Gas Oil.

Product Use: Gibson CGO is a petroleum process oil produced in the atmospheric and vacuum distillation towers and is a byproduct in the production of asphalt.

Restrictions on Use: Not available.

Manufacturer/Supplier: Gibson Energy ULC
1700, 440 – 2nd Ave. SW
Calgary, Alberta
T2P 5E9

Phone Number: (403) 206-4000

Emergency Phone: Canutec (613) 996-6666 or Cellular *666

Date of Preparation of SDS: December 5, 2017

Section 2: HAZARD(S) IDENTIFICATION

GHS INFORMATION

Classification: Carcinogenicity, Category 1B

LABEL ELEMENTS

Hazard

Pictogram(s):



Signal Word: Danger

Hazard Statements: May cause cancer.

Precautionary Statements

Prevention: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing and eye protection.

Response: If exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Hot product may cause thermal burns.

Ingredients with Unknown Toxicity: 100% of this product mixture consists of ingredient(s) of unknown acute toxicity.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR



1910.1200). This material is considered hazardous by the Hazardous Products Regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.
Gas oils (petroleum), heavy vacuum	Not available.	64741-57-7	100
Sulfur	Not available.	7704-34-9	1 - 5

Section 4: FIRST-AID MEASURES

Inhalation: If inhaled: Call a poison center or doctor if you feel unwell.
Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Eye Contact: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.
Acute and delayed symptoms and effects: May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Hot liquid product may cause serious thermal burns on direct contact.

Skin Contact: If on skin (or hair): Rinse skin with water/shower. Get immediate medical advice/attention. Remove non-adhering contaminated clothing. Cool adherent materials and burned areas with ice and/or cold water. Do not remove adherent material or clothing. Do not use solvents to remove asphalt from the skin.
Acute and delayed symptoms and effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching. Hot liquid product may cause serious thermal burns on direct contact.

Ingestion: If swallowed: Rinse mouth. Immediately call a poison center or doctor/physician. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
Acute and delayed symptoms and effects: Hot product may cause thermal burns. Causes burns to nose, mouth, throat, and digestive tract. Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea, blood in the feces and/or vomitus may also be seen.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). If exposed or concerned: Get medical advice/attention.

Note to Physicians: Symptoms may not appear immediately.



Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Not flammable or combustible by OSHA/WHMIS criteria.

- Sensitivity to Mechanical Impact:** This material is not sensitive to mechanical impact.
- Sensitivity to Static Discharge:** This material is sensitive to static discharge at temperatures at or above the flash point.

MEANS OF EXTINCTION

- Suitable Extinguishing Media:** Small Fire: Dry chemical, CO2, water spray or regular foam.
Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.
- Unsuitable Extinguishing Media:** Do not spray water onto burning product as this may cause spattering and spreading of the flame.
- Products of Combustion:** Oxides of carbon. Oxides of sulphur. Oxides of nitrogen.
- Protection of Firefighters:** Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may cause pollution. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.

Section 6: ACCIDENTAL RELEASE MEASURES

- Emergency Procedures:** Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Personal Precautions:** Do not touch or walk through spilled material. Use personal protection recommended in Section 8.
- Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways.
- Methods for Containment:** Stop leak if without risk. Contain hot liquid by dyking and allow to cool and solidify. Do not flush to sewer or allow to enter waterways.
- Methods for Clean-Up:** Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Other Information:** See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Handling:
Do not swallow. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Grounding of containers/pouring equipment is necessary when transferring hot liquid product. See Section 8 for information on Personal Protective Equipment.



Storage:

Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children. Head spaces in storage containers may contain toxic Hydrogen sulphide gas.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component

Gas oils (petroleum), heavy vacuum [CAS No. 64741-57-7]

ACGIH: A2; Exposure by all routes should be carefully controlled to levels as low as possible (2009); For Mineral oil, excluding metal working fluids; Poorly and mildly refined

OSHA: 5 mg/m³ (TWA); For Oil mist, mineral.

Sulphur [CAS No. 7704-34-9]

ACGIH: 10 mg/m³ (TWA) (Inhalable.); 3 mg/m³ (TWA) (Respirable.); For Particles (Insoluble or Poorly Soluble) Not Otherwise Specified

OSHA: 15 mg/m³ (Total dust) (TWA), 5 mg/m³ (Respirable fraction) (TWA); For Particulates Not Otherwise Regulated (PNOR).

Polycyclic aromatic hydrocarbons [CAS No. 130498-29-2]

ACGIH: A2; BEI; Exposure by all routes should be carefully controlled to levels as low as possible (1990); For Benz[a]anthracene

OSHA: 0.2 mg/m³ (TWA); For benzene-soluble fraction.

TWA: Time-Weighted Average

STEL: Short-Term Exposure Limit

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection:

Wear chemical safety goggles. If product is hot, wear full face-shield. Use equipment for eye protection that meets the standards referenced by OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.

Hand Protection:

Wear protective gloves. Nitrile or Viton® gloves are recommended. If product is hot, thermally protective gloves are recommended. Consult manufacturer specifications for further information.



Skin and Body Protection: Wear protective clothing. Clothing with full length sleeves and pants should be worn.

Respiratory Protection: If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Waxy liquid.

Colour: Dark green.

Odour: Hydrocarbon.

Odour Threshold: Not available.

Physical State: Liquid.

pH: Not available.

Melting Point / Freezing Point: Not available.

Initial Boiling Point: 259.5 °C (499.1 °F)

Boiling Range: 259.5 to 537.8 °C (499.1 to 1000 °F)

Flash Point: 129 °C (264.2 °F) (PMCC)

Evaporation Rate: Not available.

Flammability (solid, gas): Not applicable.

Lower Flammability Limit: Not available.

Upper Flammability Limit: Not available.

Vapor Pressure: < 1 kPa at 37.8 °C (100 °F) (Reid Vapour Pressure)

Vapor Density: Not available.

Relative Density: Not available.

Solubilities: Insoluble in water.

Partition Coefficient: n-Octanol/Water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Not available.



SAFETY DATA SHEET

Temperature:

Viscosity: 18.72 cSt at 40 °C (104 °F)

Percent Volatile, wt. %: Not available.

VOC content, wt. %: Not available.

Density: 912.2 kg/m³ at 15°C (59 °F)

Coefficient of Water/Oil Distribution: Not available.

Section 10: STABILITY AND REACTIVITY

Reactivity: Contact with incompatible materials. Sources of ignition. Exposure to heat.

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous Reactions: None known.

Conditions to Avoid: Contact with incompatible materials. Sources of ignition. Exposure to heat.

Incompatible Materials: Strong oxidizers. Halogens.

Hazardous Decomposition Products: Hydrogen sulphide.

Section 11: TOXICOLOGICAL INFORMATION

EFFECTS OF ACUTE EXPOSURE

Product Toxicity

Oral: Not available.

Dermal: Not available.

Inhalation: Not available.

Component Toxicity

Component	CAS No.	LD ₅₀ oral	LD ₅₀ dermal	LC ₅₀
Gas oils (petroleum), heavy vacuum	64741-57-7	Not available.	Not available.	Not available.
Sulphur	7704-34-9	> 8437 mg/kg (rat)	Not available.	Not available.
Polycyclic aromatic hydrocarbons	130498-29-2	Not available.	Not available.	Not available.

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs: Skin. Eyes. Gastrointestinal tract. Respiratory system. Bone marrow. Liver. Nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.



SAFETY DATA SHEET

Date of Preparation: December 5, 2017

- Eye:** May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision. Hot liquid product may cause serious thermal burns on direct contact.
- Skin:** May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching. Hot liquid product may cause serious thermal burns on direct contact.
- Ingestion:** Hot product may cause thermal burns. Causes burns to nose, mouth, throat, and digestive tract. Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea, blood in the feces and/or vomitus may also be seen.
- Skin Sensitization:** Not available.
- Respiratory Sensitization:** Not available.
- Medical Conditions Aggravated By Exposure:** Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

- Target Organs:** Skin. Eyes. Gastrointestinal tract. Respiratory system. Blood. Bone marrow. Liver. Nervous system. Thymus.
- Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation. Gas oils may cause damage to the blood, liver or thymus through prolonged or repeated exposure. Prolonged overexposure to Sulphur dust can produce possible skin sensitization and permanent eye damage (clouding of the lens and chronic irritation). Prolonged inhalation can cause irritation of mucous membranes. This product contains Polycyclic aromatic hydrocarbons. Prolonged contact with these compounds has been associated with the induction of skin and lung tumours, anemia, disorders of the liver, bone marrow and lymphoid tissues.
- Carcinogenicity:** May cause cancer. Gas oils cause cancer in laboratory animals.

Component Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Prop 65
Gas oils (petroleum), heavy vacuum	A2	Group 1	List 1	OSHA Carcinogen.	Listed.
Polycyclic aromatic hydrocarbons	A2	Not listed.	List 2	OSHA Carcinogen.	Listed.

- Mutagenicity:** Not available.
- Reproductive Effects:** Not available.
- Developmental Effects**
 - Teratogenicity:** Not available.
 - Embryotoxicity:** Gas oils cause fetotoxicity at doses which are maternally toxic.



Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.
Persistence / Degradability: Not available.
Bioaccumulation / Accumulation: Not available.
Mobility in Environment: Not available.
Other Adverse Effects: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions: Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

Section 14: TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

Proper Shipping Name: Not regulated.
Class: Not applicable.
UN Number: Not applicable.
Packing Group: Not applicable.
Label Code: Not applicable.

Canada Transportation of Dangerous Goods (TDG)

Proper Shipping Name: Not regulated.
Class: Not applicable.
UN Number: Not applicable.
Packing Group: Not applicable.
Label Code: Not applicable.

Section 15: REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.



Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA Title III

Component	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313	RCRA CODE	CAA 112(r) TQ (lbs.)
Polycyclic aromatic hydrocarbons	Not listed.	Not listed.	Not listed.	313^	Not listed.	Not listed.

State Regulations

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

Component	CAS No.	RTK List
Gas oils (petroleum), heavy vacuum	64741-57-7	Listed.
Sulphur	7704-34-9	Listed.
Polycyclic aromatic hydrocarbons	130498-29-2	Listed.

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

Component	CAS No.	RTK List
Gas oils (petroleum), heavy vacuum	64741-57-7	Listed.
Sulphur	7704-34-9	Listed.

Pennsylvania

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

Component	CAS No.	RTK List
Gas oils (petroleum), heavy vacuum	64741-57-7	Listed.
Sulphur	7704-34-9	Listed.
Polycyclic aromatic hydrocarbons	130498-29-2	Listed.

California

California Prop 65:



WARNING This product can expose you to chemicals including Toluene, Benzene, Ethylbenzene, and Polycyclic Aromatic Hydrocarbons which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his own particular use.

Date of Preparation of SDS: December 5, 2017

Version: 1.3

GHS SDS Prepared by: Deerfoot Consulting Inc.

Phone: (403) 720-3700